

# HEATING CIRCUIT MODULES



MIK HEATING MANIFOLD HV-3 (Order no. 840 004)

Heating circuit module HK 25-2B with insulation and overflow valve, unmixed

(Order no. 870 012) Output up to 50 kW at  $\Delta T=20^{\circ}C$ 

# Supply:

1 supply pump flange ball valve with thermometer hand dial (thermometer ring: red)

1 x pump flanged ball valve with toggle handle

> 2 x cap nut and seal 1 x overflow valve

1 x screw coupling 1"

### Return:

1 x return pump flanged ball valve with thermometer hand dial (thermometer ring: blue) and gravity brake which can be switched off by turning the hand dial 45°.

> 1 x cap nut and seal 1 x brass pipe 1 x screw coupling 1"

Can be supplied with or without pump

Distance between supports 125 mm

Heating circuit module HK 25-3B with 3-way mixer, insulation and overflow valve (Order no. 870 013)

Output up to 35 kW at  $\Delta T=20$ °C

#### Supply:

1 supply pump flange ball valve with thermometer hand dial (thermometer ring: red)

2 x cap nut and seal

1 x overflow valve

1 x 3-way mixer

1 x screw coupling 1"

# Return:

1 x return pump flanged ball valve with thermometer hand dial (thermometer ring: blue) and gravity brake which can be switched off by turning the hand dial 45°.

> 1 x cap nut and seal 1 x brass pipe

> > 1 x T piece

1 x screw coupling 1"

Can be supplied with or without

Heating circuit module HK 25-4B with 4-way mixer, insulation and overflow valve (Order no. 870 014)

Output up to 28 kW at  $\Delta T$ =20°C

## Supply:

1 supply pump flange ball valve with thermometer hand dial (thermometer ring: red)

2 x cap nut and seal

1 x overflow valve

1 x 4-way mixer

1 x screw coupling 1"

### Return:

1 x return pump flanged ball valve with thermometer hand dial (thermometer ring: blue) and gravity brake which can be switched off by turning the hand dial 45°.

> 1 x cap nut and seal 1 x brass pipe 1 x screw coupling 1"

Can be supplied with or without pump